2753 Michigan Road • Madison, Indiana 47250 • 855-743-3427

INSTALLATION INSTRUCTIONS

Full Skid Plate: Polaris Ranger XP® 900 / Polaris Ranger Crew® XP 1000



Liability Statement

SuperATV's® products are designed to best fit user's ATV/UTV under stock conditions. Adding, modifying, or fabricating any factory or aftermarket parts will void any warranty provided by SuperATV® and is not recommended. SuperATV's® products could interfere with other aftermarket accessories. If user has aftermarket products on machine, contact SuperATV® to verify that they will work together.

Although SuperATV® has thousands of satisfied customers, user should be aware that installing lift kits, long travel, or suspension kits, tires, etc. will change the ride of machine and may increase maintenance and part wear. Operating any off-road machine while, or after, consuming alcohol and/or drugs increases risk of bodily harm or death. No warranty or representation is made as to this product's ability to protect user from severe injury or death. SuperATV® urges operators and occupants to wear a helmet and appropriate riding gear at all times.

By purchasing and installing SuperATV® products, user agrees that should damages occur, SuperATV® will not be held responsible for loss of time, use, labor fees, replacement parts, or freight charges. SuperATV®, nor any 3rd party, will not be held responsible for any direct, indirect, incidental, special, or consequential damages that result from any product purchased from SuperATV®. The total liability of seller to user for all damages, losses, and causes of action, if any, shall not exceed the total purchase price paid for the product that gave rise to the claim.

SuperATV® will warranty only parts provided by SuperATV®. Any damage or problems with OEM housings, bearings, seals, or other manufacturers' products will not be covered by SuperATV®. SuperATV® parts and products are not warrantied if item was not installed properly, misused, or modified.

Installing, adding, modifying, or fabricating any factory or aftermarket product to your ATV/UTV may violate certain local, state, and federal laws. Be advised that laws vary depending on town, city, county, state, etc. Use of certain products on public streets, roads, or highways may be in violation law. The Buyer is solely and exclusively legally and personally responsible for any violation of the law by the installation or use of the product. You must abide by all local, state, and federal laws, including but not limited to vehicle safety, traffic laws, and ordinances. It is your responsibility to know the laws and how they apply to you.

The Buyer is responsible to fully understand the capability and limitations of his/her vehicle according to manufacturer specifications, warnings and instructions and agrees to hold SuperATV® harmless from any damage resulting from failure to adhere to such specifications, warnings and/ or instructions. The Buyer is also responsible to obey all applicable federal, state, and local laws and ordinances when operating his/her vehicle while using this product, and the Buyer agrees to hold SuperATV® harmless from any violation thereof.

Need help with your installation?

sales@superatv.com

www.superatv.com

1-855-743-3427

8:00am - 8:00pm EST M-Th
8:00am - 7:00pm EST Friday
9:00am - 2:00pm EST Saturday

Read instructions and view illustrations before beginning.

Thank You For Choosing SUPERATV.COM®

© 2016 SuperATV.com®. All Rights Reserved.

Rev IN-FSP-P-RAN9004 5/18/2016



(Kit contents continue on following page)

Item	Description
A*	Front Plate
B	Center Plate
C	Rear Center Plate
D	Rear Plate

Item	Description
E	Right Plate
F	Left Plate
G	Right Rear Guard
H	Left Rear Guard

Item	Description
J	Large Support Brace
K	Support Brace
L	Extension Plate

Do not install if SuperATV Frame Stiffener or Snow Plow Mount is installed.

(Kit contents continued)

4x  **M8-1.25 Nylock Nut**

2x  **M10-1.50 Nylock Nut**

4x  **M8-1.25 x 35mm Lg. BHCS**

2x  **M10-1.50 x 40mm Lg. BHCS**

4x  **1/4”-20 x 1” Lg. Self Tapping**

48x  **1/4”-20 x 1-1/2” Lg. Self Tapping**

8x  **M8 Washers**

48x  **Bowl Washer**

2x  **M12 Fender Washer**

Before installing self-tapping hardware, pre-drill holes with 5/32” drill bit.

Disregard any remaining hardware

Do not tighten hardware completey, unless noted, when installing components.

Keep all components removed from machine.

Gently flip machine onto its side and remove stock Skid Plates.



- Install Large Support Brace (J) and Support Brace (K) with hardware shown.



- Install Center Plate (B) with stock hardware.



- Install Extension Plate (L) with stock hardware.



- Install Front Plate (A) to Frame and Center Plate (B) with hardware shown.



- Install Rear Plate (D) to Frame and Extension Plate (L) with hardware shown.



- Secure Extension Plate (L) to Rear Center Plate (C), and Large Support Brace (J) with hardware shown.



- Slide Left Rear Guard (H) under Rear Plate (D) and secure to Frame with hardware shown.
- Repeat for opposite side; Right Rear Guard (G).



- Install Left Plate (F) with hardware shown.
- Repeat for opposite side; Right Plate (E).



- Install hardware shown into remaining locations.
- Tighten all hardware completely.

